




STM32Cube function pack for P-NUCLEO-IOD02A1, with IO-Link stack, IODD and control software for industrial sensors







Product summary STM32Cube function pack for P-NUCLEO-IOD02A1, with IO-Link FP-INDstack, IODD and control IODSNS1 software for industrial sensors STM32 Nucleo pack for IO-Link device P-NUCLEOapplications based on L6364Q transceiver, IOD02A1 industrial sensors and STM32L452RE MCU Industrial IO-Link device software X-CUBE-IOD02 expansion for STM32Cube Sensor and motion algorithm software X-CUBEexpansion for MEMS1 STM32Cube Industrial sensors and actuators Applications Condition Monitoring/

Features

- Firmware package to build IO-Link device applications for STM32L452REbased boards
- Middleware libraries featuring IO-Link device mini-stack for L6364Q and MEMS plus digital microphone management
- Ready-to-use binary for IO-Link device sensor data transmission
- Easy portability across different MCU families, thanks to STM32Cube
- · Free, user-friendly license terms

Description

FP-IND-IODSNS1 is an STM32Cube function pack which lets you enable IO-Link communication between P-NUCLEO-IOD02A1 kit and an IO-Link master through the L6364Q transceiver mounted on the X-NUCLEO-IOD02A1.

The function pack integrates an IO-Link demo-stack and the management of the industrial sensors mounted on the X-NUCLEO-IKS02A1.

FP-IND-IODSNS1 also includes the IODD file to be uploaded to your IO-Link master.

The software included in the package can be used in three integrated development environments (IDEs): IAR, KEIL and STM32CubeIDE.

Predictive Maintenance



Detailed description

1.1 What can you do with STM32Cube function packs?

STM32Cube function packs leverage the modularity and interoperability of STM32 Nucleo and X-NUCLEO boards together with STM32Cube and X-CUBE software to create function examples for some of the most common use cases of different application technologies.

These software function packs are designed to exploit the underlying STM32 ODE hardware and software components as much as possible to best satisfy the requirements of final user applications.

Moreover, function packs may include additional libraries and frameworks that are not present in the original X-CUBE packages, thus enabling new functionalities allowing real and usable system for developers.

1.2 What is STM32Cube?

STM32Cube is a combination of a full set of PC software tools and embedded software blocks running on STM32 microcontrollers and microprocessors:

- STM32CubeMX configuration tool for any STM32 device; it generates initialization C code for Cortex-M cores and the Linux device tree source for Cortex-A cores
- STM32CubeIDE integrated development environment based on open-source solutions like Eclipse or the GNU C/C++ toolchain, including compilation reporting features and advanced debug features
- STM32CubeProgrammer programming tool that provides an easy-to-use and efficient environment for reading, writing and verifying devices and external memories via a wide variety of available communication media (JTAG, SWD, UART, USB DFU, I2C, SPI, CAN, etc.)
- STM32CubeMonitor family of tools (STM32CubeMonRF, STM32CubeMonUCPD, STM32CubeMonPwr) to help developers customize their applications in real-time
- STM32Cube MCU and MPU packages specific to each STM32 series with drivers (HAL, low-layer, etc.), middleware, and lots of example code used in a wide variety of real-world use cases
- STM32Cube expansion packages for application-oriented solutions.

1.3 How does this function pack complement STM32Cube?

This software is based on the STM32CubeHAL. It extends STM32Cube by providing a board support package (BSP) for IO-Link communication through the X-NUCLEO-IOD02A1 and the data management of the industrial sensors mounted on the X-NUCLEO-IKS02A1.

The drivers abstract low-level details of the hardware and allow the middleware components and applications to access data in a hardware-independent manner.

The package includes some middleware libraries to enable an IO-Link demo stack. Developers can prototype an IO-Link device (sensor node) running on an STM32 microcontroller to acquire sensor data from an IO-Link master where the IODD in the function pack has been uploaded.

DB4338 - Rev 2 page 2/4



Revision history

Table 1. Document revision history

Date	Version	Changes
04-Dec-2020	1	Initial release.
14-Feb-2024	2	Updated title and Section 1.3: How does this function pack complement STM32Cube?.

DB4338 - Rev 2 page 3/4



IMPORTANT NOTICE - READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgment.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2024 STMicroelectronics – All rights reserved

DB4338 - Rev 2 page 4/4