


Isolated thyristors driver in AC solid-state-relay



Features

- Isolated thyristor driver STSID140-12
 - 1250 V RMS of insulation barrier (V_{ISO})
 - 40 mA output current for thyristor gate
 - Power transfer from low voltage
 - Direct MCU driving with I/O at 3.3 V
- Compact AC solid state-relay
 - Up to 4 Amps AC load driving
 - TN5015H-8G high temperature 50 Amps 800 V
 - SCRs in back-to-back
 - Compact D2PAK SMD package
- AC main zeros cross-triggering option
- 5-pins LV connectors for MCU control
- Two HV connectors for load and line connection

Description

The [STEVAL-SID140V1](#) allows to evaluate insulated control of thyristors SCRs with the [STSID140-12](#) driver.

The [STSID140-12](#) driver has a 40 mA of output current capability to drive SCR gate easily without any additional power supply in high voltage.


The galvanic-insulated inductive barrier allows a 1250 V rms rating-insulated voltage, compliant for the application of functional insulation, and with a high creepage distance at 3.9 mm.

Based on two [TN5015H-8G](#) SCR in back-to-back, this evaluation board is able to drive AC load connected on line up 4 Amps.

Product summary	
Isolated thyristors driver in AC solid-state-relay	STEVAL-SID140V1
Surface Mount Isolated Thyristor Driver	STSID140-12
50 A 800 V High Temperature SCR in D2PAK package	TN5015H-8G
Applications	Heating control Induction motor control Residential smart plug

Schematic diagrams

Figure 1. STEVAL-SID140V1 circuit schematic



2 Board versions

Table 1. STEVAL-SID140V1 versions

Finished good	Schematic diagrams	Bill of materials
STV\$SID140V1A ⁽¹⁾	STV\$SID140V1A schematic diagrams	STV\$SID140V1A bill of materials

1. This code identifies the STEVAL-SID140V1 evaluation board first version.

Revision history

Table 2. Document revision history

Date	Revision	Changes
24-Sep-2025	1	Initial release.

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice.

In the event of any conflict between the provisions of this document and the provisions of any contractual arrangement in force between the purchasers and ST, the provisions of such contractual arrangement shall prevail.

The purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgment.

The purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of the purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

If the purchasers identify an ST product that meets their functional and performance requirements but that is not designated for the purchasers' market segment, the purchasers shall contact ST for more information.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2025 STMicroelectronics – All rights reserved