


Rad-hard plastic Hex inverter with Schmitt trigger input

TSSOP-20



Product status link

LEOAC14

Features

- Schmitt trigger input
- 1.65 V to 6 V operating supply
- 7 V max. rating
- Nickel/palladium/gold-lead-finished (NiPdAu), whisker-free
- Gold-wires
- RML < 1% and CVCN < 0.1% guaranteed outgassing
- 50 krad (Si) total ionizing dose
- SEL-free up to 62.5 MeV.cm²/mg
- Mass: 80 mg
- Compliant with ST-LEO-specification

Application

- Low earth orbit (LEO) applications

Description


The **LEOAC14** is a CMOS low power hex inverter qualified for use in aerospace environments. It operates from 1.65 V to 6 V power supply (7 V absolute maximum ratings). Each operator features a Schmitt trigger input that is capable of transforming slowly changing input signals into sharp output signals.

The **LEOAC14** can operate over a large temperature range of -40 °C to +125 °C and it is housed in a plastic TSSOP-20, thin-shrink small outline package, 20 leads, using gold-wires and nickel/palladium/golden-lead-finishing to prevent whiskers.

The **LEOAC14** is compliant with ST-LEO-specification, dedicated specification for space-ready rad-hard plastic products. This AEC-Q100-based specification offers a specific trade-off between footprint size savings, cost of ownership and quality assurance together with radiation hardness and large quantity capability.

1 Functional description

Figure 1. Pin connections (top view)



Note: NC: not internally connected. The pin can be externally connected to any potential.

Table 1. Input and output gate

Each gate	
INPUT (A)	OUTPUT (Y)
H	L
L	H

with: L = low level, H = high level.

For all inputs, $V_{IN} = V_{IH}$ minimum or V_{IL} maximum, verify output V_{OUT} .

2 Maximum ratings and operating conditions

Table 2. Absolute maximum ratings

Symbol	Parameter	Value	Unit
VCC ⁽¹⁾	Maximum power supply between VCC and GND	-0.5 to 7	V
VIN	DC input voltage range	-0.5 to VCC+0.5 (and 7 V max.)	V
VOUT	DC output voltage range	-0.5 to VCC+0.5 (and 7 V max.)	V
IK	I/O clamp diode current	+/-20	mA
T _{stg}	Maximum temperature storage	-65 to 150	°C
T _j ⁽²⁾	Maximum junction temperature	+150	°C
R _{th} ⁽³⁾	Junction-to-ambient thermal resistance (Θ _{ja})	80	°C/W
	Junction-to-case thermal resistance (Θ _{jc})	17	°C/W
ESD	HBM (human body model)	2 k	V
	CDM (charged device model)	1 k	

1. All voltages, except differential I/O bus voltage, are with respect to the network ground terminal.
2. Maximum junction temperature shall not be exceeded except for allowable short duration burn-in screening conditions as per the method 5004 of MIL-STD-883.
3. Short-circuits can cause excessive heating. Destructive dissipation can result from short-circuits on the amplifiers.

Note: Absolute maximum ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied. All values are referred to GND.

Table 3. Operating conditions

Symbol	Parameter	Min.	Max.	Unit
VCC	Analog supply voltage	1.65	6	V
VIN	Input voltage range	0	VCC	V
VOUT	Output voltage range	0	VCC	V
T _a	Ambient temperature range	-40	+125	°C

Note: All unused inputs must be held at VCC or GND to ensure proper device operation.

3 Electrical characteristics

VCC = 3 V to 5.5 V, typical values are at ambient $T_a = +25\text{ }^{\circ}\text{C}$, minimum and maximum values are at $T_a = -40\text{ }^{\circ}\text{C}$ and $+125\text{ }^{\circ}\text{C}$, unless otherwise specified.

Table 4. Electrical characteristics

Symbol	Parameter	Test conditions	VCC	Min.	Typ.	Max.	Unit
VOH ⁽¹⁾	High level output voltage	For all inputs affecting output under test, VIN = VIH minimum or VIL maximum For all other inputs, VIN = VCC or GND, IOH = -50 μA	3 V	2.9			V
			4.5 V	4.4			
			5.5 V	5.4			
		For all inputs affecting output under test, VIN = VIH minimum or VIL maximum. For all other inputs, VIN = VCC or GND, IOH = -12 mA	3 V	2.4			
			4.5 V	3.7			
		For all inputs affecting output under test, VIN = VIH minimum or VIL maximum. For all other inputs, VIN = VCC or GND, IOH = -24 mA	5.5 V	4.7			
VOL ⁽¹⁾	Low level output voltage	For all inputs affecting output under test, VIN = VIH minimum or VIL maximum. For all other inputs, VIN = VCC or GND, IOL = +50 μA	3 V			0.1	V
			4.5 V			0.1	
			5.5 V			0.1	
		For all inputs affecting output under test, VIN = VIH minimum or VIL maximum. For all other inputs, VIN = VCC or GND, IOL = +12 mA	3 V			0.5	
			4.5 V			0.5	
		For all inputs affecting output under test, VIN = VIH minimum or VIL maximum. For all other inputs, VIN = VCC or GND, IOL = +24 mA	5.5 V			0.5	
IOH	High level output current		3 V	-12			mA
			4.5 V	-24			
			5.5 V	-24			
IOL	Low level output current		3 V			12	
			4.5 V			24	
			5.5 V			24	
VIH	High level input voltage		3 V	2.1			V
			4.5 V	3.15			
			5.5 V	3.85			
VIL	Low level input voltage		3 V			0.9	
			4.5 V			1.35	
			5.5 V			1.65	

Symbol	Parameter	Test conditions	VCC	Min.	Typ.	Max.	Unit
VT+	Positive-going threshold voltage		3 V			2.2	V
			4.5 V			3.2	
			5.5 V			3.9	
VT-	Negative-going threshold voltage		3 V	0.5			V
			4.5 V	0.9			
			5.5 V	1.1			
VHYS	Hysteresis voltage		3 V	0.3		1.2	V
			4.5 V	0.4		1.4	
			5.5 V	0.5		1.6	
VIC+	Positive input clamp voltage	For input under test, IIN = 1 mA	0 V	0.4		1.5	V
VIC-	Negative input clamp voltage	For input under test, IIN = -1.0 mA	Open	-0.4		-1.5	V
IIH	Input current high	For input under test, VIN = VCC For all other inputs, VIN = VCC or GND	5.5 V			1	μA
IIL	Input current low	For input under test, VIN = GND For all other inputs, VIN = VCC or GND	5.5 V			-1	μA
ICCH	Quiescent supply current, output high	For all inputs, VIN = VCC or GND IOUT = 0 A	5.5 V			40	μA
ICCL	Quiescent supply current, output low	For all inputs, VIN = VCC or GND IOUT = 0 A	5.5 V			40	μA
CIN ⁽²⁾	Input capacitance	Ta=+25 °C	5 V			8	pF
CPD ⁽²⁾⁽³⁾	Power dissipation capacitance	Ta=+25 °C, F=1 MHz	5 V			50	pF
Tr, Tf	Output rise time and fall time	CL = 2 pF, RL = 500 ohm, see Figure 2. Waveform	3 V		3.3		ns
			4.5 V		2.7		
		CL = 50 pF, RL = 500 ohm, see Figure 2. Waveform	3 V		4.6		
			4.5 V		3.3		
tPHL ⁽⁴⁾	Propagation delay time An to Yn, high to low	CL = 50 pF, RL = 500 ohm See Figure 2. Waveform	3 V	1		14	ns
			4.5 V	1		10	
tPLH ⁽⁴⁾	Propagation delay time An to Yn, low to high	CL = 50 pF, RL = 500 ohm See Figure 2. Waveform	3 V	1		16	
			4.5 V	1		12	

1. The VOH and VOL tests are performed at VCC = 3.0 V and 4.5 V. The VOH and VOL tests are guaranteed, if not tested, for other values of VCC. The limits shown apply to operation at VCC = 3.3 V ±0.3 V and VCC = 5.0 V ±0.5 V. Tests with input current at +50 mA and -50 mA are performed on only one input at a time with duration not to exceed 10 ms. Transmission driving tests may be performed using VIN = VCC or GND. When VIN = VCC or GND is used, the test is guaranteed for VIN = VIH minimum and VIL maximum.
2. CIN and CPD shall be measured only for initial qualification and after process or design changes which may affect capacitance. CIN shall be measured between the designated terminal and GND at a frequency of 1 MHz. CPD shall be tested in accordance with the latest revision of JEDEC standard JESD20 and table 1A herein. For CIN and CPD, test all applicable pins on five devices with zero failures.
3. Power dissipation capacitance (CPD) determines both the power consumption (PD) and dynamic current consumption (IS). Where: PD = (CPD + CL) (VCC x VCC) f + (ICC x VCC) and IS = (CPD + CL) VCC x f + ICC, and f is the frequency of the input signal and CL is the external output load capacitance.

4. *The AC limits at $V_{CC} = 5.5\text{ V}$ are equal to the limits at $V_{CC} = 4.5\text{ V}$ and guaranteed by testing at $V_{CC} = 4.5\text{ V}$. The AC limits at $V_{CC} = 3.6\text{ V}$ are equal to the limits at $V_{CC} = 3.0\text{ V}$ and guaranteed by testing at $V_{CC} = 3.0\text{ V}$. Minimum AC limits for $V_{CC} = 5.5\text{ V}$ and $V_{CC} = 3.6\text{ V}$ are 1.0 ns and guaranteed by guard banding the $V_{CC} = 4.5\text{ V}$ and $V_{CC} = 3.0\text{ V}$ minimum limits, respectively, to 1.5 ns . For propagation delay tests, all paths must be tested.*

4 Waveform and test circuit

Figure 2. Waveform





Figure 3. Test circuit



Note:

- When measuring t_{PHL} or t_{PLH} : V_{TEST} = open.
- C_L = 50 pF minimum or equivalent (includes probe and jig capacitance).
- R_L = 500 Ω or equivalent.
- Input signal from pulse generator: V_{IN} = 0.0 V to V_{CC} ; $PRR \leq 1$ MHz; $Z_O = 50 \Omega$; $t_r \leq 3.0$ ns; $t_f \leq 3.0$ ns; t_r and t_f is measured from 10% of V_{CC} to 90% of V_{CC} and from 90% of V_{CC} to 10% of V_{CC} , respectively; duty cycle = 50 percent.
- Timing parameters are tested at a minimum input frequency of 1 MHz.
- The outputs are measured one at a time with one transition per measurement.

5 Radiations

Total ionizing dose (TID):

For the qualification, the product is characterized in TID as per MIL-STD-883 TM 1019 up to 50 krad(Si) on 5 biased parts at high dose rate; such a rate being the worst condition for a pure CMOS technology.

All parameters provided in [Table 4. Electrical characteristics](#) apply to both pre- and post-irradiation.

Each new production lot is tested at high dose rate as per MIL-STD-883 TM 1019 on 5 parts.

Heavy-ions:

Single event latchup (SEL) is characterized at 125 °C at a LET of 62.5 MeV.cm²/mg. The test shows the product is immune to heavy ions at this LET. Heavy-ion trials are performed on qualification lots only.

The results in radiation are summarized in [Table 5. Radiations](#) as follows:

Table 5. Radiations

Symbol	Characteristics	Value
TID ⁽¹⁾	<ul style="list-style-type: none"> High-dose rate (40 rad (Si) / h) Temperature: 25 °C Performed on 5 biased parts 	Within Table 4. Electrical characteristics up to 50 krad(Si)
SEL ⁽²⁾	<ul style="list-style-type: none"> LET: 62.5 MeV.cm²/mg (Xenon ions) Temperature: 125 °C Fluence: 1 x 10⁷ ions/cm² (10 Million of particles per cm²) Normal incidence 	Immune to SEL up to 62.5 MeV.cm ² /mg

1. A total ionizing dose (TID) of 50 krad(Si) is equivalent to 500 Gy(Si), (1 gray = 100 rad).

2. SEL: single event latchup.



6 Outgassing

Specification (tested per ASTM E 595)	Value	Unit
Recovered mass loss (RML) ⁽¹⁾	0.06	%
Collected volatile condensable material (CVCM) ⁽²⁾	0.00	%

1. RML < 1%.
2. CVCM < 0.1%.

7 Package information

To meet environmental requirements, ST offers these devices in different grades of **ECOPACK** packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions, and product status are available at: www.st.com. ECOPACK is an ST trademark.

7.1 TSSOP-20 package information

Figure 4. TSSOP-20 package outline




Table 6. TSSOP-20 package mechanical data

Symbol	Millimeters			Inches ⁽¹⁾		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A			1.2			0.047
A1	0.05		0.15	0.002	0.004	0.006
A2	0.8	1	1.05	0.031	0.039	0.041
b	0.19		0.30	0.007		
c	0.09		0.20	0.004		
D	6.4	6.5	6.6	0.252	0.256	0.260
E	6.2	6.4	6.6	0.244	0.252	0.260
E1	4.3	4.4	4.48	0.169	0.173	0.176
e		0.65 BSC			0.0256 BSC	
K	0°		8°	0°		8°
L	0.45	0.60	0.75	0.018	0.024	0.030

1. Values in inches are converted from mm and rounded to 4 decimal digits.

7.2 TSSOP-20 packing information

Figure 5. TSSOP-20 Carrier tape (dimensions in mm) outline





Figure 6. TSSOP-20 tape (dimensions in mm) outline



8 Ordering information


Table 7. Ordering information

Order code	Quality level	Package	Lead-finish	Marking	Packing
LEOAC14PT-D	Development sample	TSSOP-20	NiPdAu	DLEOAC14	Tape and reel
LEOAC14PT	Flight model	TSSOP-20	NiPdAu	LEOAC14	Tape and reel

Table 8. Order code

LEO	AC14	P	T
LEO qualification	Name	TSSOP-20 package	Tape and reel

Figure 7. TSSOP-20 marking



- a: pin-1 reference
- A : Second Level of interconnexion (type of lead-finishing)
- B: ST logo
- C: Assy plant
- D: Lot code
- E: Marking area
- F: Country of origin
- G: Assy year
- H: Assy week

Revision history

Table 9. Document revision history

Date	Version	Changes
10-Feb-2021	1	Initial release.
29-Mar-2021	2	Updated Section 8 Ordering information. Removed "Product documentation" section.
08-Jun-2021	3	Updated Tstg value in Table 2 and TID characteristics in Table 5.
30-Aug-2021	4	Updated Section 5 Radiations.
10-Jan-2022	5	Removed ICCT parameter in Table 4.
04-Oct-2024	6	Updated minimum operating power supply from 2 V to 1.65 V.

Contents

1	Functional description	2
2	Maximum ratings and operating conditions	3
3	Electrical characteristics	4
4	Waveform and test circuit	7
5	Radiations	8
6	Outgassing	9
7	Package information	10
7.1	TSSOP-20 package information	10
7.2	TSSOP-20 packing information	11
8	Ordering information	13
	Revision history	14

List of tables

Table 1.	Input and output gate	2
Table 2.	Absolute maximum ratings	3
Table 3.	Operating conditions	3
Table 4.	Electrical characteristics	4
Table 5.	Radiations	8
Table 6.	TSSOP-20 package mechanical data	10
Table 7.	Ordering information.	13
Table 8.	Order code	13
Table 9.	Document revision history	14

List of figures

Figure 1.	Pin connections (top view)	2
Figure 2.	Waveform	7
Figure 3.	Test circuit	7
Figure 4.	TSSOP-20 package outline	10
Figure 5.	TSSOP-20 Carrier tape (dimensions in mm) outline.	11
Figure 6.	TSSOP-20 tape (dimensions in mm) outline	12
Figure 7.	TSSOP-20 marking	13

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgment.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2024 STMicroelectronics – All rights reserved