STB45N30M5

Datasheet

N-channel 300 V, 53 A, 37 mΩ typ., MDmesh M5 Power MOSFET in a D²PAK package



D²PAK



Features

Order code	V_{DS}	$R_{DS(on)}$ max.	I_D
STP45N30M5	300 V	40 mΩ	53 A

- 100% avalanche tested
- Excellent switching performance
- Extremely low $R_{DS(on)}$
- Low gate charge and input capacitance

Applications

- Switching applications

Description

This device is an N-channel Power MOSFET based on the MDmesh M5 innovative vertical process technology combined with the well-known PowerMESH horizontal layout. The resulting product offers extremely low on-resistance, making it particularly suitable for applications requiring high power and superior efficiency.

Product status link
STB45N30M5

Product summary	
Order code	STB45N30M5
Marking	45N30M5
Package	D²PAK
Packing	Tape and reel

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{GS}	Gate-source voltage	±25	V
I_D	Drain current (continuous) at T_C = 25 °C	53	A
	Drain current (continuous) at T_C = 100 °C	34	
I_{DM}(1)	Drain current (pulsed)	212	A
P_{TOT}	Total dissipation at T_C = 25 °C	250	W
dv/dt(2)	Peak diode recovery voltage slope	15	V/ns
T_{stg}	Storage temperature range	-55 to 150	°C
T_J	Operating junction temperature range		

1. *Pulse width is limited by safe operating area.*
2. *I_{SD} ≤ 53 A, di/dt ≤ 400 A/µs, V_{DS} peak < $V_{(BR)DSS}$, V_{DD} = 240 V*

Table 2. Thermal data

Symbol	Parameter	Value	Unit
R_{thJC}	Thermal resistance, junction-to-case	0.5	°C/W
R_{thJA}(1)	Thermal resistance, junction-to-ambient	30	

1. *When mounted on a standard 1-inch² area of FR-4 PCB with 2-oz copper.*

Table 3. Avalanche characteristics

Symbol	Parameter	Value	Unit
I_{AR}	Avalanche current, repetitive or not repetitive (pulse width limited by T_J max)	16	A
E_{AS}	Single pulse avalanche energy (starting T_J = 25 °C, I_D = I_{AR}, V_{DD} = 50 V)	550	mJ

2 Electrical characteristics

T_C = 25 °C unless otherwise specified

Table 4. On-/off-states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	V_{GS}= 0 V, I_D = 1 mA	300			V
I_{DSS}	Zero gate voltage drain current	V_{GS} = 0 V, V_{DS} = 300 V			1	µA
		V_{GS} = 0 V, V_{DS} = 300 V, T_C = 125 °C(1)			100	µA
I_{GSS}	Gate body leakage current	V_{DS} = 0 V, V_{GS} = ±25 V			±100	nA
$V_{GS(th)}$	Gate threshold voltage	V_{DS} = V_{GS}, I_D = 250 µA	3	4	5	V
$R_{DS(on)}$	Static drain-source on-resistance	V_{GS} = 10 V, I_D = 26.5 A		37	40	mΩ

1. *Specified by design, not tested in production.*

Table 5. Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C_{iss}	Input capacitance	V_{DS} = 100 V, f = 1 MHz, V_{GS} = 0 V	-	4240	-	pF
C_{oss}	Output capacitance		-	205	-	pF
C_{rss}	Reverse transfer capacitance		-	9.5	-	pF
$C_{o(tr)}$(1)	Time-related equivalent capacitance	V_{DS} = 0 to 240 V, V_{GS} = 0 V	-	373	-	pF
$C_{o(er)}$(2)	Energy-related equivalent capacitance		-	202	-	pF
R_g	Gate input resistance	f = 1 MHz, I_D = 0 A	-	1.4	-	Ω
Q_g	Total gate charge	V_{DD} = 240 V, I_D = 24 A, V_{GS} = 0 to 10 V (see Figure 15. Test circuit for gate charge behavior)	-	95	-	nC
Q_{gs}	Gate-source charge		-	23	-	nC
Q_{gd}	Gate-drain charge		-	37	-	nC

1. *$C_{o(tr)}$ is a constant capacitance value that gives the same charging time as Coss while V_{DS} is rising from 0 to 80% V_{DSS}.*
2. *$C_{o(er)}$ is a constant capacitance value that gives the same stored energy as C_{oss} while V_{DS} is rising from 0 to 80% V_{DSS}.*

Table 6. Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(v)}$	Voltage delay time	V_{DD} = 240 V, I_D = 32 A, R_G = 4.7 Ω, V_{GS} = 10 V (see Figure 16. Test circuit for inductive load switching and diode recovery times and Figure 19. Switching time waveform)	-	66	-	ns
$t_{r(v)}$	Voltage rise time		-	15	-	ns
$t_{f(i)}$	Current fall time		-	24	-	ns
$t_{c(off)}$	Crossing time		-	22.5	-	ns

Table 7. Source-drain diode

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
I_{SD}	Source-drain current		-		53	A
I_{SDM}(1)	Source-drain current (pulsed)		-		212	A
V_{SD}(2)	Forward on voltage	I_{SD} = 53 A, V_{GS} = 0 V	-		1.5	V
t_{rr}	Reverse recovery time	I_{SD} = 48 A, di/dt = 100 A/µs, V_{DD} = 60 V (see Figure 16. Test circuit for inductive load switching and diode recovery times)	-	223		ns
Q_{rr}	Reverse recovery charge		-	2.5		µC
I_{RRM}	Reverse recovery current		-	23		A
t_{rr}	Reverse recovery time	I_{SD} = 48 A, di/dt = 100 A/µs, V_{DD} = 60 V, T_j = 150 °C (see Figure 16. Test circuit for inductive load switching and diode recovery times)	-	280		ns
Q_{rr}	Reverse recovery charge		-	3.9		µC
I_{RRM}	Reverse recovery current		-	28		A

1. *Pulse width limited by safe operating area*
2. *Pulsed: pulse duration = 300 µs, duty cycle 1.5%*

2.1 Electrical characteristics (curves)

Figure 1. Safe operating area



Figure 2. Thermal impedance



Figure 3. Output characteristics



Figure 4. Transfer characteristics



Figure 5. Gate charge vs gate-source voltage



Figure 6. Static drain-source on-resistance



Figure 7. Capacitance variations



Figure 8. Output capacitance stored energy



Figure 9. Normalized gate threshold voltage vs temperature



Figure 10. Normalized on-resistance vs temperature



Figure 11. Normalized $V_{(BR)DSS}$ vs temperature



Figure 12. Source-drain diode forward characteristics



Figure 13. Switching energy vs gate resistance

(1)



1. *Eon including reverse recovery of a SiC diode.*

3 Test circuits

Figure 14. Test circuit for resistive load switching times



AM01468v1

Figure 15. Test circuit for gate charge behavior



AM01469v1

Figure 16. Test circuit for inductive load switching and diode recovery times



AM01470v1

Figure 17. Unclamped inductive load test circuit



AM01471v1

Figure 18. Unclamped inductive waveform



AM01472v1

Figure 19. Switching time waveform



AM05540v2

4 Package information

To meet environmental requirements, ST offers these devices in different grades of ECOPACK packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions, and product status are available at: www.st.com. ECOPACK is an ST trademark.

4.1 D²PAK (TO-263) type A2 package information

Figure 20. **D²PAK (TO-263) type A2 package outline**



0079457_A2_27

Table 8. D²PAK (TO-263) type A2 package mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.40		4.60
A1	0.03		0.23
b	0.70		0.93
b2	1.14		1.70
c	0.45		0.60
c2	1.23		1.36
D	8.95		9.35
D1	7.50	7.75	8.00
D2	1.10	1.30	1.50
E	10.00		10.40
E1	8.70	8.90	9.10
E2	7.30	7.50	7.70
e		2.54	
e1	4.88		5.28
H	15.00		15.85
J1	2.49		2.69
L	2.29		2.79
L1	1.27		1.40
L2	1.30		1.75
R		0.40	
V2	0°		8°

Figure 21. D²PAK (TO-263) recommended footprint (dimensions are in mm)



4.2 D²PAK packing information

Figure 22. D²PAK tape drawing (dimensions are in mm)



Revision history

Table 9. **Document revision history**

Date	Version	Changes
16-May-2018	1	Initial release
16-Oct-2025	2	Updated Section 4: Package information.

Contents

1 **Electrical ratings** 2
2 **Electrical characteristics** 3
2.1 Electrical characteristics (curves) 5
3 **Test circuits** 8
4 **Package information** 9
4.1 D²PAK (TO-263) type A2 package information 9
4.2 D²PAK packing information 11
Revision history 12

IMPORTANT NOTICE – READ CAREFULLY

STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice.

In the event of any conflict between the provisions of this document and the provisions of any contractual arrangement in force between the purchasers and ST, the provisions of such contractual arrangement shall prevail.

The purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST’s terms and conditions of sale in place at the time of order acknowledgment.

The purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of the purchasers’ products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

If the purchasers identify an ST product that meets their functional and performance requirements but that is not designated for the purchasers' market segment, the purchasers shall contact ST for more information.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2025 STMicroelectronics – All rights reserved